

RESIDENTIAL BATTERY

IonHome Series

IH10



Class-A LiFePO4
Battery Cell



Flexible Expansion
Capability



Intelligent
Software BMS



Support C&I and
Residential

DATASHEET

Model	IH10
Main Parameters	
Battery Type	LiFePO4
Nominal Voltage (V)	51.2
Nominal Capacity (Ah)	200
Nominal Energy (kWh)	10.24
Operating Voltage Range (V)	44~58
Maximum series connection quantity	16 in Series
Max. Continuous Charge Current (A)	150
Peak Charge Current (A)	153A@3s
Max. Continuous Discharge Current (A)	150
Peak Discharge Current (A)	160A@1s
Recommended Depth of Discharge	90%
-Cycle Life of Battery Cell	>6000@25°C, 0.5C/0.5C, 80%DOD, 80%EOL
Communication Port	CAN/RS485
General Parameters	
Dimensions (D*W*H, mm)	415.5*240*708.2
Net Weight (kg)	85±5
Operating Temperature/Charge (°C)	0~+60
Operating Temperature/Discharge (°C)	-10~+65
Recommend Operating Temperature (°C)	15~+35
Storage Temperature (°C)	0~+35
Humidity	10%~95%
Altitude (m)	2000
Ingress Protection	IP20
Cooling Method	Natural Cooling
Shell Material	Metal
LCD Display	4.3-inch touch screen (color)
WiFi	Yes
Bluetooth	Yes
Certification	IEC62619/UN38.3/MSDS/DGM
Protection	
Circuit Breaker	Yes
Fuse	NO
Voltage Protection	Yes
Current Protection	Yes
Temperature Protection	Yes
Short Circuit Protection	Yes

This material is for reference only and does not constitute any commitment regarding product performance or specifications. Product design and specifications may be changed at any time.

The Company assumes no liability for any losses arising from the use of this material or the products